



ZLPWF - STANDARD TEFZEL JACKET SILICONE ELASTOMER FIBERS		
ACTIVE DIAMETER FROM 100 TO 500 [MICRONS]	ACTIVE DIAMETER FROM 500 TO 1000 [MICRONS]	ACTIVE DIAMETER MORE THEN 1000 [MICRONS]
ZLPWF100/150T//270	ZLPWF600/750T//1010	
ZLPWF200/300T//450	ZLPWF800/950T//1400	
ZLPWF300/440T//660	ZLPWF1000/1150T//1650	
ZLPWF400/550T//850		

- NOTES:
1. HERAEUS INFRASIL 301 ROAD .
 2. EXCELLENT TRANSMISSION IN THE RANGE 400-2200 NM.
 3. HIGH POWER LASER TRANSMISSION.
 4. STRESS PROOF LOAD 100KPSI.
 5. OPERATION TEMPERATURE FROM -40°C TO +150°C



OTHER FIBER DIMENSION AVAILABLE ON REQUEST.
PLEASE CONTACT US FOR DISCUSSIONS.



FIBER CODE EXPLANATION

ZLPWF **200** / **300** **B** T// **450** - **0.37**


PURE FUSED SILICA CORE [MICRONS] SILICONE ELASTOMER COATING [MICRONS] TEFZEL JACKET [MICRONS] NUMERICAL APERATURE [NA]

JACKET COLOR

NATURAL
B BLACK

0.37 STANDARD, NA=0.37± 0.02

OTHER FIBER DIMENSION AVAILABLE ON REQUEST.
PLEASE CONTACT US FOR DISCUSSIONS.



TITLE: ZLPWF - TEFZEL JACKET SILICONE ELASTOMER FIBERS		
SIZE: A3	DRAWING NO.: ZLPWF-002-00	REV.: A
FILE NAME: ZLPWF-TEFZEL.idw	ITEM NO.:	
COMPANY: Z-LIGHT, LTD.	CODE NO.:	
HOME PAGE: HTTP://WWW.Z-LIGHT.LV	ORDER NO.:	
SCALE: DO NOT SCALE	DIMENSIONS ARE IN MM	SHEET 1 OF 1